

Swarfega® Powerwash Formula

Multi-Purpose Vehicle Traffic Film Remover

PRODUCT DESCRIPTION

A caustic containing alkaline detergent vehicle cleaner for the rapid removal of road film, oils and greases.

WHERE TO USE

TFR for excellent economic cleaning performance across a wide range of vehicle types. Medium soiling levels.

INSTRUCTIONS FOR USE

By hand: Wet vehicle thoroughly, rinsing off excess mud and grime. Dilute 1 part to up to 200 parts water and mix well. Wash using a soft cloth, sponge or brush. Rinse well and dry with chamois leather. Wear protective gloves/protective clothing/eye protection/face protection.

Automatic Washers: If using gantry wash or spray arch: add to detergent feed system as supplied or pre-dilute 50:50 with water, dependent on the degree of cleaning required. Adjust detergent flow to 0.5 - 1.0%. Allow the equipment to run through its cleaning programme. This packaging is recyclable or can be disposed of, if well drained, as normal domestic or industrial waste. Safety data sheet available for professional user on request.

Pressure Washers: If using fixed box-jet or portable pressure washer: add to detergent feed system as supplied or pre-dilute 1 part with up to 7 parts water, dependant upon the degree of cleaning required.

- 1. Pre-wet vehicle thoroughly using clean water, ensuring vehicle surface is cool before cleaning commences
- 2. If using a high pressure lance, hold 50cm/18 inches from vehicle surface; if using a foaming lance, stand at least 2m/6 feet away from surface
- 3. For best results clean one section at a time, working from the bottom upwards
- 4. Do not allow product to dry on to exterior bodywork
- 5. Rinse thoroughly with clean water, working fron the top downwards
- May affect certain non-factory paint finishes; if unsure test on a small hidden area first.



FEATURES	BENEFITS
Ready to Use	Without the need for pre-diluting with water for maximum power and convenience.
Prevents Scaling	Contains water softeners to help prevent scaling and help prolong equipment life.
Powerful	Rapidly removes all types of general road grime.
Economical	Can be pre-diluted 50:50 with water to make 50 litres of TFR.
Versatile Formula	Product is suitable for use on bodywork, engines and chassis.
Free Rinsing	Gives fast, effective rinse off helping to leave a non-smear, streak-free finish.
Silicate Free	Prevents etching of glass or damage to original paint finishes when used correctly.
Equipment Compatible	With all hot and cold vehicle cleaning equipment.

PACK SIZES

STOCK CODE	SIZE
PFO25L	25 litres

SC Johnson Professional Ltd. Denby Hall Way Denby Derbyshire DE5 8JZ UK

Tel: +44 (0) 1773 855100 www.scip.com This information and all further technical advice is based upon our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments.